

Colt XL8

OUTSTANDING OUTDOOR
PERFORMANCE WITH
LUXURIOUS FEATURES

COLT XL8

The **Colt XL8** features a powerful drive train and large 33 cm (13") wheels to handle rugged outdoor terrain. Luxury touches like a wraparound delta tiller, low profile non-marking tyres and LED kerb light blend seamlessly giving the Colt XL8 a sleek, sporty style.




Pride[®]
Mobility Products Ltd.

(Tel) 01869 324 600 • (Fax) 01869 323 070 • www.pride-mobility.co.uk

Colt XL8

Weight capacity:	181 kg (28.5 Stone)
Maximum speed ¹ :	Up to 13 km/h (8 mph)
Ground clearance ² :	8 cm (3")
Turning radius:	150 cm (59")
Overall length ² :	135 cm (53")
Overall width ² :	63.5 cm (25")
Front tyres:	10 cm x 33 cm (4" x 13")
Rear tyres:	10 cm x 33 cm (4" x 13")
Suspension:	Front & rear
Maximum obstacle climbing ability:	10 cm (4")
Total Weight Without Batteries:	94 kg (207 lbs.)
Heaviest piece when disassembled:	front section
Standard seating:	Type: Captains style, fold flat seat Weight: 20 kg (45 lbs.) Material: Black Vinyl Dimensions: width – 46 cm (18") depth – 46 cm (18")
Drive System:	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Dual Braking System:	Electronic, regenerative, and electromechanical
Battery Requirements ³ :	Two 12-volt, deep cycle Size: 50 AH or 70 AH (optional) Weight: 50 AH: 17 kg (38 lbs.) each/ 70 AH: 24.27 kg (53.5 lbs.)
Battery Charger:	8-amp, off-board

Colours:



Features

- Large 33 cm (13") solid tyres for excellent outdoor performance
- Full lighting package including directional signals and angle-adjustable, LED headlight
- Delta tiller with wrap-around handles
- Front basket standard
- Easily accessible tie down points (for transport of unoccupied scooter)
- Rear view mirror standard

Options

- Forearm crutch holder
- Cane/crutch holder
- Wishbone crutch holder
- Oxygen tank holder
- Rear basket
- Safety flag
- Walker holder
- 70 AH batteries

¹Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition.

²Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

³AGM or Gel-Cell type required.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; due to the manufacturers commitment to constant improvement and development, they reserve the right to alter specifications without prior notice. Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressure, ambient temperature, and the gradient and surface of the road or pavement.